

## LED PLL : DIRECT FIT

### DESCRIPTION

LED PLL Replacement Lamps directly replace compact fluorescent PLL lamps at a fraction of the energy cost.

### FEATURES

- Directly replace 40W CFL PLL lamps
- Solid state replacement for 2' 40W PLL compact fluorescent lamps with 2G11 base
- Frosted lens for uniform diffuse appearance
- Up to 50% instant energy savings
- Instant-On with no warm up like fluorescents
- Suitable for use in totally enclosed fixtures
- No rewiring or modifications to fixture of any kind required
- Frosted glass lens reduces visual glare
- Not compatible with emergency ballasts
- Note: check eiko.com for ballast compatibility

### WARRANTY

- 5 year limited warranty; see eiko.com for warranty details

### APPLICATIONS

- Retail
- Hospitality
- Office
- Ceiling Luminaires



RoHS  
Compliant

FC

cUL US LISTED

|                     |                       |                                    |
|---------------------|-----------------------|------------------------------------|
| <b>PERFORMANCE</b>  | Power Consumption     | 23W                                |
|                     | Lumens                | 2,600/2,800                        |
|                     | Efficacy (LPW)        | 113/122                            |
|                     | CRI                   | 80+                                |
|                     | Beam                  | 220°                               |
|                     | CCT                   | 3000K, 3500K, 4000K, 5000K         |
|                     | Life (L70)            | 50,000 hours                       |
| <b>ELECTRICAL</b>   | Power Factor          | ≥0.9                               |
|                     | THD                   | <20%                               |
|                     | Input Voltage         | 120-277V                           |
| <b>CONSTRUCTION</b> | Operating Temperature | -4°F to 113°F (-20°C to 45°C)      |
|                     | Base                  | 2G11                               |
| <b>LISTINGS</b>     | Certification(s)      | cULus Listed; FCC; LM70            |
|                     | Material Usage        | RoHS Compliant; no mercury or lead |
|                     | Environment           | UL Listed for damp locations       |

## PERFORMANCE SUMMARY

| Order Code | Item #              | Lumens | Watts | CCT   | CRI | MOL   | Base | Life/Hours | Replaces Fluor |
|------------|---------------------|--------|-------|-------|-----|-------|------|------------|----------------|
| 60461      | LED23W/PLL/830-G7DR | 2,600  | 23W   | 3000K | 80+ | 22.2" | 2G11 | 50K        | 40W CFL PLL    |
| 60462      | LED23W/PLL/835-G7DR | 2,600  | 23W   | 3500K | 80+ | 22.2" | 2G11 | 50K        | 40W CFL PLL    |
| 60463      | LED23W/PLL/840-G7DR | 2,800  | 23W   | 4000K | 80+ | 22.2" | 2G11 | 50K        | 40W CFL PLL    |
| 60464      | LED23W/PLL/850-G7DR | 2,800  | 23W   | 5000K | 80+ | 22.2" | 2G11 | 50K        | 40W CFL PLL    |

NOTE: Use order code when ordering.

## DIMENSIONS



