

Image Not Found

CE and RoHS Certified, and UL listed, Eiko LitespanLED® PAR lamps come in a variety of shapes and bases, as well as an assortment of wattages and color temperatures, ideal for a wider range of applications. Dimmable to 5% for design flexibility and lifetimes exceeding 40,000 hours. Up to 80% electricity savings compared to halogen lamps!

LitespanLED® PAR Lamps								
Ordering Code	Watts	Shape	Base	Lumens	MOL	MOD	Rated Life	Approvals
LED13WPAR38/NFL/830K-DIM-G6	13	PAR38	Medium Screw (E26)	1050	5.16/131	4.72/120	25,000	cULus, RoHS Compliant
LED12WPAR30S/NFL/840-DIM-G4A	12	PAR30S	Medium Screw (E26)	850	3.62/92	3.74/95	25,000	cULus
LED11WPAR30/NFL/827K-DIM-G6	11	PAR30	Medium Screw (E26)	850	4.57/116	3.74/95	25,000	cULus, Energy Star, RoHS Compliant
LED11WPAR30/NFL/830K-DIM-G6	11	PAR30	Medium Screw (E26)	850	4.57/116	3.74/95	25,000	cULus, Energy Star, RoHS Compliant
LED11WPAR30/FL/827K-DIM-G6	11	PAR30	Medium Screw (E26)	850	4.57/116	3.74/95	25,000	cULus, Energy Star, RoHS Compliant
LED7WPAR16/NFL/827K-DIM-G5	7	PAR16	Medium Screw (E26)	490	2.87/73	1.97/50	25,000	cULus, Energy Star
LED7WPAR16/NFL/830K-DIM-G5	7	PAR16	Medium Screw (E26)	490	2.87/73	1.97/50	25,000	cULus, Energy Star
LED7WPAR16/NFL/840K-DIM-G5	7	PAR16	Medium Screw (E26)	490	2.87/73	1.97/50	25,000	cULus, Energy Star
LED7WPAR16/FL/827K-DIM-G5	7	PAR16	Medium Screw (E26)	490	2.87/73	1.97/50	25,000	cULus, Energy Star
LED7WPAR16/FL/830K-DIM-G5	7	PAR16	Medium Screw (E26)	490	2.87/73	1.97/50	25,000	cULus, Energy Star
LED7WPAR16/FL/840K-DIM-G5	7	PAR16	Medium Screw (E26)	490	2.87/73	1.97/50	25,000	cULus, Energy Star
LED20WPAR38/FL/827K-DIM-G6	20	PAR38	Medium Screw (E26)	1700	5.16/131	4.72/120	25,000	cULus, Energy Star, RoHS Compliant
LED20WPAR38/FL/830K-DIM-G6	20	PAR38	Medium Screw (E26)	1700	5.16/131	4.72/120	25,000	cULus, Energy Star, RoHS Compliant
LED20WPAR38/FL/840K-DIM-G6	20	PAR38	Medium Screw (E26)	1700	5.16/131	4.72/120	25,000	cULus, Energy Star, RoHS Compliant
LED11WPAR30/FL/830-DIM-G8	11	PAR30	Medium Screw (E26)	850	4.57/116	3.74/95	25,000	cULus, Energy Star, FCC
LED11WPAR30/FL/840-DIM-G8	11	PAR30	Medium Screw (E26)	850	4.57/116	3.74/95	25,000	cULus, FCC
LED11WPAR30/NFL/827-DIM-G8	11	PAR30	Medium Screw (E26)	850	4.57/116	3.74/95	25,000	cULus, FCC
LED11WPAR30/NFL/830-DIM-G8	11	PAR30	Medium Screw (E26)	850	4.57/116	3.74/95	25,000	cULus, FCC
LED11WPAR30/NFL/840-DIM-G8	11	PAR30	Medium Screw (E26)	850	4.57/116	3.74/95	25,000	cULus, FCC
LED11WPAR30/FL/827-DIM-G8	11	PAR30	Medium Screw (E26)	850	4.57/116	3.74/95	25,000	cULus, Energy Star, FCC
LED11WPAR30/FL/850-DIM-G8	11	PAR30	Medium Screw (E26)	850	4.57/116	3.74/95	25,000	cULus, FCC
LED15WPAR38/FL/830-DIM-G8	15	PAR38	Medium Screw (E26)	1250	5.16/131	4.72/120	25,000	cULus, Energy Star, FCC
LED15WPAR38/FL/840-DIM-G8	15	PAR38	Medium Screw (E26)	1250	5.16/131	4.72/120	25,000	cULus, FCC

LitespanLED® PAR Lamps								Continued...	
Ordering Code	Watts	Shape	Base	Lumens	MOL	MOD	Rated Life	Approvals	
LED15WPAR38/FL/850-DIM-G8	15	PAR38	Medium Screw (E26)	1250	5.16/131	4.72/120	25,000	cULus, FCC	
LED15WPAR38/FL/827-DIM-G8	15	PAR38	Medium Screw (E26)	1250	5.16/131	4.72/120	25,000	cULus, FCC	
LED15WPAR38/NFL/827-DIM-G8	15	PAR38	Medium Screw (E26)	1250	5.16/131	4.72/120	25,000	cULus, FCC	
LED15WPAR38/NFL/830-DIM-G8	15	PAR38	Medium Screw (E26)	1250	5.16/131	4.72/120	25,000	cULus, FCC	
LED15WPAR38/NFL/840-DIM-G8	15	PAR38	Medium Screw (E26)	1250	5.16/131	4.72/120	25,000	cULus, FCC	
LED7WPAR20/FL/827-DIM-G8	7	PAR20	Medium Screw (E26)	500	3.19/81	2.48/63	25,000	cULus, Energy Star	
LED7WPAR20/FL/830-DIM-G8	7	PAR20	Medium Screw (E26)	500	3.19/81	2.48/63	25,000	cULus, Energy Star	
LED7WPAR20/FL/840-DIM-G8	7	PAR20	Medium Screw (E26)	500	3.19/81	2.48/63	25,000	cULus, Energy Star	
LED7WPAR20/NFL/827-DIM-G8	7	PAR20	Medium Screw (E26)	500	3.19/81	2.48/63	25,000	cULus	
LED7WPAR20/NFL/830-DIM-G8	7	PAR20	Medium Screw (E26)	500	3.19/81	2.48/63	25,000	cULus, Energy Star	
LED7WPAR20/NFL/840-DIM-G8	7	PAR20	Medium Screw (E26)	500	3.19/81	2.48/63	25,000	cULus, Energy Star	
LED11WPAR30S/FL/827-DIM-G8	11	PAR30S	Medium Screw (E26)	850	3.62/92	3.74/95	25,000	cULus, Energy Star, FCC	
LED11WPAR30S/FL/830-DIM-G8	11	PAR30S	Medium Screw (E26)	850	3.62/92	3.74/95	25,000	cULus, Energy Star, FCC	
LED11WPAR30S/FL/840-DIM-G8	11	PAR30S	Medium Screw (E26)	850	3.62/92	3.74/95	25,000	cULus, Energy Star, FCC	
LED11WPAR30S/NFL/827-DIM-G8	11	PAR30S	Medium Screw (E26)	850	3.62/92	3.74/95	25,000	cULus, Energy Star, FCC	
LED11WPAR30S/NFL/830-DIM-G8	11	PAR30S	Medium Screw (E26)	850	3.62/92	3.74/95	25,000	cULus, Energy Star, FCC	
LED11WPAR30S/NFL/840-DIM-G8	11	PAR30S	Medium Screw (E26)	850	3.62/92	3.74/95	25,000	cULus, FCC	
LED5.5WPAR20/FL/927-DIM-G9	5.5	PAR20	Medium Screw (E26)	500	3.15/80	2.48/63	25000	cULus, CEC	
LED5.5WPAR20/FL/930-DIM-G9	5.5	PAR20	Medium Screw (E26)	500	3.15/80	2.48/63	25000	cULus, CEC	
LED10WPAR30/FL/927-DIM-G9	10	PAR30	Medium Screw (E26)	900	4.53/115	3.74/95	25000	cULus, CEC	
LED10WPAR30/FL/930-DIM-G9	10	PAR30	Medium Screw (E26)	900	4.53/115	3.74/95	25000	cULus, CEC	
LED12WPAR38/FL/927-DIM-G9	12	PAR38	Medium Screw (E26)	1200	5.12/130	4.72/120	25000	cULus, CEC	
LED12WPAR38/FL/930-DIM-G9	12	PAR38	Medium Screw (E26)	1200	5.12/130	4.72/120	25000	cULus, CEC	
LED13WPAR38/FL/830K-DIM-G6	13	PAR38	Medium Screw (E26)	1050	5.16/131	4.72/120	25,000	cULus, Energy Star, RoHS Compliant	
LED13WPAR38/FL/840K-DIM-G6	13	PAR38	Medium Screw (E26)	1050	5.16/131	4.72/120	25,000	cULus, Energy Star, RoHS Compliant	

## NOTES:

---



---



---



---