

LED A15 & A19



A15
E26



A19
E26



A19
GU24



A15 Colored
E26

5-15
watts

replaces
40-100W
incan

GU24
or E26
base

240°/
300°
beam

Features

- Direct replacement for 40, 60, 75, 100W incandescent A lamps
- 300° Omni beam angle is ideal for table lamps, wall sconces, and luminous globe fixtures
- 80% more efficient and 30x longer life than standard incandescent
- Smooth, clean outside housing
- Compatible with a wide array of dimmers
- Comfortable diffused light
- Instant-On with no warm up, unlike CFLs
- Available in 2700K, 3000K, 4000K and 5000K
- Shatter-resistant plastic housing for reduced risk of injury and breakage



Performance

- 6W replaces 40W incandescent
- 8/9/9.5W replaces 60W incandescent
- 11W replaces 75W incandescent
- 15W replaces 100W incandescent
- 120V @ 60Hz
- Standard series 80+ CRI for enhanced color and lighting uniformity from lamp to lamp
- ANSI construction compliant
- Suitable for damp locations
- 50,000 hour design life
- Select items enclosed fixture rated
- Not for use with electronic timers, photocells, or motion/occupancy sensors
- Contains no mercury or lead; classified as non-hazardous waste
- -20° C (-4° F) to 40° C (104° F) operating temperature

Applications

- Restaurants & Hospitality
- Retail
- Residential
- Accent/Display Lighting
- Healthcare



LitespanLED® A Lamps								
Ordering Code	Watts	Shape	Base	Lumens	MOL	MOD	Rated Life	Approvals
LED15WA19/OMN/827-GU24-DIM-G8								
LED15WA19/OMN/830-GU24-DIM-G8								
LED15WA19/OMN/840-GU24-DIM-G8								
LED9WA19/OMN/827-GU24-DIM-G9	9	A19	GU24	800	4.21/106.9	2.36/59.9	25000	cULus, Energy Star, FCC
LED9WA19/OMN/830-GU24-DIM-G9	9	A19	GU24	800	4.21/106.9	2.36/59.9	25000	cULus, Energy Star, FCC
LED11WA19/OMN/827-GU24-DIM-G9	11	A19	GU24	1100	4.21/106.9	2.36/59.9	25000	cULus, Energy Star, FCC
LED11WA19/OMN/830-GU24-DIM-G9	11	A19	GU24	1100	4.21/106.9	2.36/59.9	25000	cULus, Energy Star, FCC
LED11WA19/OMN/840-GU24-DIM-G9	11	A19	GU24	1100	4.21/106.9	2.36/59.9	25000	cULus, Energy Star, FCC
LED9WA19/OMN/827-GU24-DIM-A	9	A19	GU24	800	4.25/108	2.36/60	25000	cULus, Energy Star, RoHS Compliant
LED9WA19/OMN/830-GU24-DIM-A	9	A19	GU24	800	4.25/108	2.36/60	25000	cULus, Energy Star, RoHS Compliant
LED9WA19/OMN/840-GU24-DIM-A	9	A19	GU24	800	4.25/108	2.36/60	25000	cULus, Energy Star, RoHS Compliant
LED11WA19/OMN/827-GU24-DIM-A	11	A19	GU24	1100	4.25/108	2.36/60	25000	cULus, Energy Star, RoHS Compliant
LED11WA19/OMN/830-GU24-DIM-A	11	A19	GU24	1100	4.25/108	2.36/60	25000	cULus, Energy Star, RoHS Compliant
LED11WA19/OMN/840-GU24-DIM-A	11	A19	GU24	1100	4.25/108	2.36/60	25000	cULus, Energy Star, RoHS Compliant
LED15WA19/OMN/827-DIM-A	15	A19	Medium Screw (E26)	1600	4.61/117	2.36/60	25000	cULus, Energy Star, RoHS Compliant
LED15WA19/OMN/830-DIM-A	15	A19	Medium Screw (E26)	1600	4.61/117	2.36/60	25000	cULus, Energy Star, RoHS Compliant
LED15WA19/OMN/840-DIM-A	15	A19	Medium Screw (E26)	1600	4.61/117	2.36/60	25000	cULus, Energy Star, RoHS Compliant
LED15WA19/OMN/850-DIM-A	15	A19	Medium Screw (E26)	1600	4.61/117	2.36/60	25000	cULus, Energy Star, RoHS Compliant
LED11WA19/OMN/827-DIM-A	11	A19	Medium Screw (E26)	1100	4.25/108	2.36/60	25000	cULus, Energy Star, RoHS Compliant
LED11WA19/OMN/830-DIM-A	11	A19	Medium Screw (E26)	1100	4.25/108	2.36/60	25000	cULus, Energy Star, RoHS Compliant
LED11WA19/OMN/840-DIM-A	11	A19	Medium Screw (E26)	1100	4.25/108	2.36/60	25000	cULus, Energy Star, RoHS Compliant
LED11WA19/OMN/850-DIM-A	11	A19	Medium Screw (E26)	1100	4.25/108	2.36/60	25000	cULus, Energy Star, RoHS Compliant
LED6WA19/OMN/827-DIM-G9	6	A19	Medium Screw (E26)	480	4.21/106.9	2.36/59.9	25000	cULus, Energy Star, FCC
LED6WA19/OMN/830-DIM-G9	6	A19	Medium Screw (E26)	480	4.21/106.9	2.36/59.9	25000	cULus, Energy Star, FCC
LED6WA19/OMN/840-DIM-G9	6	A19	Medium Screw (E26)	480	4.21/106.9	2.36/59.9	25000	cULus, Energy Star, FCC
LED9WA19/OMN/827-DIM-G9	9	A19	Medium Screw (E26)	800	4.21/106.9	2.36/59.9	25000	cULus, Energy Star, FCC
LED9WA19/OMN/830-DIM-G9	9	A19	Medium Screw (E26)	800	4.21/106.9	2.36/59.9	25000	cULus, Energy Star, FCC
LED9WA19/OMN/840-DIM-G9	9	A19	Medium Screw (E26)	800	4.21/106.9	2.36/59.9	25000	cULus, Energy

LitespanLED® A Lamps								Continued...
Ordering Code	Watts	Shape	Base	Lumens	MOL	MOD	Rated Life	Approvals
G9								Star, FCC
LED9WA19/OMN/850-DIM-G9	9	A19	Medium Screw (E26)	800	4.21/106.9	2.36/59.9	25000	cULus, Energy Star, FCC
LED6WA19/OMN/827-DIM-A	6	A19	Medium Screw (E26)	480	4.25/108	2.36/60	25000	cULus, Energy Star, RoHS Compliant
LED6WA19/OMN/830-DIM-A	6	A19	Medium Screw (E26)	480	4.25/108	2.36/60	25000	cULus, Energy Star, RoHS Compliant
LED6WA19/OMN/840-DIM-A	6	A19	Medium Screw (E26)	480	4.25/108	2.36/60	25000	cULus, Energy Star, RoHS Compliant
LED9WA19/OMN/827-A	9	A19	Medium Screw (E26)	800	4.25/108	2.36/60	25000	cULus, Energy Star, RoHS Compliant
LED9WA19/OMN/830-A	9	A19	Medium Screw (E26)	800	4.25/108	2.36/60	25000	cULus, Energy Star, RoHS Compliant
LED9WA19/OMN/840-A	9	A19	Medium Screw (E26)	800	4.25/108	2.36/60	25000	cULus, Energy Star, RoHS Compliant
LED9WA19/OMN/850-A	9	A19	Medium Screw (E26)	800	4.25/108	2.36/60	25000	cULus, Energy Star, RoHS Compliant
LED9WA19/OMN/827-DIM-A	9	A19	Medium Screw (E26)	800	4.25/108	2.36/60	25000	cULus, Energy Star, RoHS Compliant
LED9WA19/OMN/830-DIM-A	9	A19	Medium Screw (E26)	800	4.25/108	2.36/60	25000	cULus, Energy Star, RoHS Compliant
LED9WA19/OMN/840-DIM-A	9	A19	Medium Screw (E26)	800	4.25/108	2.36/60	25000	cULus, Energy Star, RoHS Compliant
LED9WA19/OMN/850-DIM-A	9	A19	Medium Screw (E26)	800	4.25/108	2.36/60	25000	cULus, Energy Star, RoHS Compliant
LED15WA19/OMN/827-DIM-G9	15	A19	Medium Screw (E26)	1600	4.61/117.1	2.36/59.9	25000	cULus, Energy Star, FCC
LED9WA19/OMN/827-DIM-G8	9	A19	Medium Screw (E26)	800	4.21/108	2.36/60	25,000	cULus, Energy Star, FCC
LED6WA19/OMN/830-G8	6	A19	Medium Screw (E26)	480	4.33/110	2.36/60	15,000	cULus
LED6WA19/OMN/840-G8	6	A19	Medium Screw (E26)	480	4.33/110	2.36/60	15,000	cULus
LED11WA19/OMN/827-DIM-G8	11	A19	Medium Screw (E26)	1100	4.33/110	2.36/60	25,000	cULus, Energy Star, FCC
LED6WA19/OMN/827-G8	6	A19	Medium Screw (E26)	480	4.33/110	2.36/60	15,000	cULus, Energy Star, FCC
LED9.5WA19/OMN/827-G8	9.5	A19	Medium Screw (E26)	800	4.33/110	2.36/60	15,000	cULus, Energy Star, FCC
LED11WA19/OMN/830-DIM-G8	11	A19	Medium Screw (E26)	1100	4.33/110	2.36/60	25,000	cULus, Energy Star
LED11WA19/OMN/840-DIM-G8	11	A19	Medium Screw (E26)	1100	4.33/110	2.36/60	25,000	cULus, Energy Star
LED9.5WA19/OMN/830-G8	9.5	A19	Medium Screw (E26)	800	4.33/110	2.36/60	15,000	cULus, Energy Star
LED9.5WA19/OMN/840-G8	9.5	A19	Medium Screw (E26)	800	4.33/110	2.36/60	15,000	cULus, Energy Star
LED11WA19/OMN/850-DIM-G8	11	A19	Medium Screw (E26)	1100	4.33/110	2.36/60	25,000	cULus, Energy Star
LED5WA15/OMN/BLUE-G8	5	A15	Medium Screw (E26)		3.58/91	1.89/48	10,000	cULus
LED5WA15/OMN/RED-G8	5	A15	Medium Screw (E26)		3.58/91	1.89/48	10,000	cULus
LED5WA15/OMN/YELLOW-G8	5	A15	Medium Screw (E26)		3.58/91	1.89/48	10,000	cULus
LED19WA21/OMN/830-G8	19	A21	Medium Screw (E26)	2000	5.551/141	2.638/67	25000	cULus, Energy Star
LED19WA21/OMN/840-G8	19	A21	Medium Screw (E26)	2000	5.551/141	2.638/67	25000	cULus, Energy Star
LED19WA21/OMN/850-G8	19	A21	Medium Screw (E26)	2000	5.551/141	2.638/67	25000	cULus, Energy Star
LED25WA21/OMN/830-G8	25	A21	Medium Screw (E26)	2550	5.472/139	2.638/67	25000	cULus, Energy

