



BR LAMPS : BR20, BR30, BR40

DESCRIPTION

LED BR Replacement Lamps directly replace incandescent BR lamps at a fraction of the energy cost.

FEATURES

- 80% more efficient and 30x longer life than standard incandescent
- Smooth body with ANSI standard form factor
- +25,000 hour rated life for ENERGY STAR® Approved lamps*
- 50,000 hour design life**
- Acceptable for ICAT rated downlights
- Shatter resistant for reduced risk of injury and breakage

WARRANTY

- 5 year limited warranty; see eiko.com for warranty details

APPLICATIONS

- Recessed Lighting
- Accent / Display Lighting
- Retail / Residential
- Hospitality
- Track Lighting
- Healthcare
- Office
- Hotel



* Early initial qualification for ENERGY STAR allows for directional lamp life claims of 25,000 hours (L70) with 3,000 hour actual test data, LM80 data and in-situ temperature measurements. As the lamps pass ENERGY STAR requirements, manufacturers may increase the lifetime of a product as dictated by ENERGY STAR guidelines. See http://www.energystar.gov/index.cfm?fuseaction=products_for_partners.showLightbulbs for further details.

** Design life is based on engineering testing and probability analysis



PERFORMANCE	Power Consumption	7W	11W	12W	17W
	Lumens	550	850	1,050	1,400
	Efficacy (LPW)	79	77	88	82
	CRI	80+			
	Beam	120°			
	CCT	2700K, 3000K, 4000K, 5000K			
	Life (L70)	25,000 hours*			
ELECTRICAL	Power Factor	≥0.9			
	Input Voltage	120V			
CONSTRUCTION	Base	E26			
LISTINGS	Certification(s)	ENERGY STAR® Rated; cULus Classified			
	Material Usage	RoHS Compliant; no mercury or lead			
	Environment	Dry and damp location rated			

PERFORMANCE SUMMARY

BR20:

Order Code	Item #	Lumens	Watts	CCT	CRI	Beam	MOL	MOD	Life/Hours	Replaces Incan.	ES
10763	LED7WBR20/827-DIM-G9	550	7W	2700K	80+	120°	3.82"	2.5"	25,000	55W R20	★
10764	LED7WBR20/830-DIM-G9	550	7W	3000K	80+	120°	3.82"	2.5"	25,000	55W R20	★
10765	LED7WBR20/840-DIM-G9	550	7W	4000K	80+	120°	3.82"	2.5"	25,000	55W R20	★

BR30:

Order Code	Item #	Lumens	Watts	CCT	CRI	Beam	MOL	MOD	Life/Hours	Replaces Incan.	ES
10375	LED8WBR30/827-DIM-G9	650	8W	2700K	80+	120°	5.12"	3.74"	25,000	65W BR30	★
10376	LED8WBR30/830-DIM-G9	650	8W	3000K	80+	120°	5.12"	3.74"	25,000	65W BR30	★
10377	LED8WBR30/840-DIM-G9	650	8W	4000K	80+	120°	5.12"	3.74"	25,000	65W BR30	★
10747	LED11WBR30/827-DIM-G9	850	11W	2700K	80+	120°	5.12"	3.74"	25,000	65W BR30	★
10748	LED11WBR30/830-DIM-G9	850	11W	3000K	80+	120°	5.12"	3.74"	25,000	65W BR30	★
10749	LED11WBR30/840-DIM-G9	850	11W	4000K	80+	120°	5.12"	3.74"	25,000	65W BR30	★
10756	LED11WBR30/850-DIM-G9	850	11W	5000K	80+	120°	5.12"	3.74"	25,000	65W BR30	★

BR40:

Order Code	Item #	Lumens	Watts	CCT	CRI	Beam	MOL	MOD	Life/Hours	Replaces Incan.	ES
10757	LED12WBR40/827-DIM-G9	1,050	12W	2700K	80+	120°	6.26"	4.72"	25,000	80W BR40	★
10758	LED12WBR40/830-DIM-G9	1,050	12W	3000K	80+	120°	6.26"	4.72"	25,000	80W BR40	★
10759	LED12WBR40/840-DIM-G9	1,050	12W	4000K	80+	120°	6.26"	4.72"	25,000	80W BR40	★
10760	LED17WBR40/827-DIM-G9	1,400	17W	2700K	80+	120°	6.26"	4.72"	25,000	100W BR40	★
10761	LED17WBR40/830-DIM-G9	1,400	17W	3000K	80+	120°	6.26"	4.72"	25,000	100W BR40	★
10762	LED17WBR40/840-DIM-G9	1,400	17W	4000K	80+	120°	6.26"	4.72"	25,000	100W BR40	★

NOTE: Use order code when ordering. ★ENERGY STAR Rated

DIMENSIONS

