



## A15/A19 REPLACEMENT : E26 BASE

### DESCRIPTION

LED A-Line Replacement Lamps directly replace incandescent A lamps at a fraction of the energy cost.

### FEATURES

- Direct replacement for 40W, 60W, 75W, or 100W incandescent A-lamps
- 300° Omni beam angle is ideal for table lamps, wall sconces, and luminous globe fixtures
- 80% more efficient and 30x longer life than standard incandescent
- Shatter-resistant plastic housing for reduced risk of injury and breakage
- Compatible with a wide array of dimmers
- ANSI construction compliant
- Not for use with electronic timers, photocells, or motion/occupancy sensors

### WARRANTY

- 5 year limited warranty; see eiko.com for warranty details

### APPLICATIONS

- Restaurants & Hospitality
- Retail
- Residential
- Accent/Display Lighting
- Healthcare



A15  
E26



A19  
E26



A19  
GU24



A15 Colored  
E26



<b>PERFORMANCE</b>	Power Consumption	5W	6W	8W	9W/9.5W	11W	15W
	Lumens	-	480	800	800	1,100	1,600
	Efficacy (LPW)	-	80	100	89	100	107
	CRI	80+					
	Beam	240°/300°					
	CCT	2700K/3000K/4000K/5000K					
	Life (L70)	10,000/15,000/25,000 hours					
<b>ELECTRICAL</b>	Power Factor	>0.7					
	Input Voltage	120V					
<b>CONSTRUCTION</b>	Operating Temperature	-4°F to 104°F (-20°C to 40°C)					
	Base	E26					
<b>LISTINGS</b>	Certification(s)	ENERGY STAR® Rated; cULus Classified					
	Material Usage	RoHS Compliant; no mercury or lead					
	Environment	Suitable for damp locations; Enclosed fixture rated (select items)					

# PERFORMANCE SUMMARY

## A15 MEDIUM BASE (E26):

Order Code	Item #	Lumens	Watts	LPW	CCT	CRI	Beam	MOL	MOD	Life/Hours	Replaces Incan.	ES
09976	LED5WA15/OMN/BLUE-G9	-	5W		Blue	-	300°	3.58"	1.89"	10K	-	
09981	LED5WA15/OMN/RED-G8	-	5W		Red	-	300°	3.58"	1.89"	10K	-	
09973	LED5WA15/OMN/YELLOW-G9*	-	5W		Yellow	-	300°	3.58"	1.89"	10K	-	
10057	LED8WA15/OMN/827-DIM-G8*	800	8W		2700K	80+	240°	3.49"	1.97"	25K	60W A15	★
10058	LED8WA15/OMN/830-DIM-G8*	800	8W		3000K	80+	240°	3.49"	1.97"	25K	60W A15	★
10059	LED8WA15/OMN/840-DIM-G8*	800	8W		4000K	80+	240°	3.49"	1.97"	25K	60W A15	★

## A19 MEDIUM BASE (E26):

Order Code	Item #	Lumens	Watts	LPW	CCT	CRI	Beam	MOL	MOD	Life/Hours	Replaces Incan.	ES
09882	LED6WA19/OMN/827-DIM-G8*	480	6W		2700K	80+	300°	4.21"	2.36"	25K	40W A19	★
09887	LED6WA19/OMN/827-G8*	480	6W		2700K	80+	300°	4.33"	2.36"	25K	40W A19	★
09750	LED6WA19/OMN/830-G8*	480	6W		3000K	80+	300°	4.33"	2.36"	25K	40W A19	★
09751	LED6WA19/OMN/840-G8*	480	6W		4000K	80+	300°	4.33"	2.36"	25K	40W A19	★
09748	LED6WA19/OMN/830-DIM-G8*	480	6W		3000K	80+	300°	4.33"	2.36"	25K	40W A19	★
09749	LED6WA19/OMN/840-DIM-G8*	480	6W		4000K	80+	300°	4.33"	2.36"	25K	40W A19	★
09895	LED9WA19/OMN/827-DIM-G8*	800	9W		2700K	80+	300°	4.21"	2.36"	25K	60W A19	★
09896	LED9WA19/OMN/830-DIM-G8*	800	9W		3000K	80+	300°	4.21"	2.36"	25K	60W A19	★
09752	LED9WA19/OMN/840-DIM-G8*	800	9W		4000K	80+	300°	4.21"	2.36"	25K	60W A19	★
10060	LED9WA19/OMN/850-DIM-G8*	800	9W		5000K	80+	300°	4.21"	2.36"	25K	60W A19	★
09889	LED9.5WA19/OMN/827-G8*	800	9.5W		2700K	80+	300°	4.33"	2.36"	25K	60W A19	
09753	LED9.5WA19/OMN/830-G8*	800	9.5W		3000K	80+	300°	4.33"	2.36"	25K	60W A19	★
09941	LED9.5WA19/OMN/840-G8*	800	9.5W		4000K	80+	300°	4.33"	2.36"	25K	60W A19	★
09885	LED11WA19/OMN/827-DIM-G8*	1,100	11W		2700K	80+	300°	4.33"	2.36"	25K	75W A19	★
09942	LED11WA19/OMN/830-DIM-G8*	1,100	11W		3000K	80+	300°	4.33"	2.36"	25K	75W A19	★
09943	LED11WA19/OMN/840-DIM-G8*	1,100	11W		4000K	80+	300°	4.33"	2.36"	25K	75W A19	★
10061	LED11WA19/OMN/850-DIM-G8*	1,100	11W		5000K	80+	300°	4.33"	2.36"	25K	75W A19	★
09886	LED15WA19/OMN/827-DIM-G8*	1,600	15W		2700K	80+	300°	4.33"	2.36"	25K	100W A19	★
09944	LED15WA19/OMN/830-DIM-G8*	1,600	15W		3000K	80+	300°	4.33"	2.36"	25K	100W A19	★
09945	LED15WA19/OMN/840-DIM-G8*	1,600	15W		4000K	80+	300°	4.33"	2.36"	25K	100W A19	★
09946	LED15WA19/OMN/850-DIM-G8*	1,600	15W		5000K	80+	300°	4.33"	2.36"	25K	100W A19	★

## A19 GU24 BASE:

Order Code	Item #	Lumens	Watts	LPW	CCT	CRI	Beam	MOL	MOD	Life/Hours	Replaces Incan.	ES
09974	LED9WA19/OMN/827-GU24-DIM-G8	800	9W		2700K	80+	300°	4.25"	2.36"	25K	60W A19	★
09975	LED9WA19/OMN/830-GU24-DIM-G8	800	9W		3000K	80+	300°	4.25"	2.36"	25K	60W A19	★
10108	LED9WA19/OMN/840-GU24-DIM-G8	800	9W		4000K	80+	300°	4.25"	2.36"	25K	60W A19	★
10122	LED11WA19/OMN/827-GU24-DIM-G8	1,100	11W		2700K	80+	300°	4.25"	2.36"	15K	75W A19	★
10014	LED11WA19/OMN/830-GU24-DIM-G8	1,100	11W		3000K	80+	300°	4.25"	2.36"	15K	75W A19	★
10100	LED11WA19/OMN/840-GU24-DIM-G8	1,100	11W		4000K	80+	300°	4.25"	2.36"	15K	75W A19	★
10125	LED15WA19/OMN/830-GU24-DIM-G8 †	1,600	15W		3000K	80+	300°	4.25"	2.36"	15K	75W A19	★

NOTE: Use order code when ordering. \*Enclosed fixture rated. †Canada only. ★ENERGY STAR® Rated