



LED HID REPLACEMENT : SMALL

DESCRIPTION

LED HID Replacement Lamps directly replace high-watt HID fixtures at a fraction of the energy cost.

FEATURES

- LED replacement for high wattage HID fixtures from 50W to 100W
- Consumes up to 80% less energy than conventional HID systems
- State-of-the-art LED light sources deliver over 130 lumens per watt
- Lasts 3x longer than metal halide or HPS HID lamps
- Shatter resistant for reduced risk of injury & breakage
- Integral driver, eliminates the need for external driver or ballast
- Suitable for use in totally enclosed fixtures
- Direct line voltage 100-277V - not compatible with ballasts
- Non-dimmable
- Universal mounting position
- UL1598C – Existing fixtures retain UL certification

WARRANTY

- 5 year limited warranty; see eiko.com for warranty details

APPLICATIONS

- Bollards
- Wallpacks
- Downlights



RoHS
Compliant

FC

CLASSIFIED
UL
US

	Power Consumption	15W	19W	24W
PERFORMANCE	Lumens	1,875/1,950	2,375/2,470	3,000/3,120
	Efficacy (LPW)	125/130	125/130	125/130
	CRI	80+		
	CCT	3000K, 4000K, 5000K		
	Life (L70)	50,000 hours		
ELECTRICAL	Power Factor	≥0.9		
	THD	<20%		
	Input Voltage	100-277V		
CONSTRUCTION	Operating Temperature	-40°F to 140°F (-40°C to 60°C)		
	Base	E26		
LISTINGS	Certification(s)	cULus Classified		
	Material Usage	RoHS Compliant; no mercury or lead		
	Environment	Damp location rated		

PERFORMANCE SUMMARY

Order Code	Item #	Lumens	Watts	CCT	CRI	Volts	Base	Life/Hours	Replaces HID	LDL
09632	LED15WPT30KMED-G7	1,875	15W	3000K	80+	100-277V	E26	50K	50W	
09390	LED15WPT40KMED-G7	1,875	15W	4000K	80+	100-277V	E26	50K	50W	✘
09391	LED15WPT50KMED-G7	1,950	15W	5000K	80+	100-277V	E26	50K	50W	✘
09633	LED19WPT30KMED-G7	2,375	19W	3000K	80+	100-277V	E26	50K	70W	
09392	LED19WPT40KMED-G7	2,375	19W	4000K	80+	100-277V	E26	50K	70W	✘
09393	LED19WPT50KMED-G7	2,470	19W	5000K	80+	100-277V	E26	50K	70W	✘
09634	LED24WPT30KMED-G7	3,000	24W	3000K	80+	100-277V	E26	50K	100W	

NOTE: Use order code when ordering. ✘Lighting Design Lab Qualified

DIMENSIONS

