



LED PLL : DIRECT FIT

DESCRIPTION

LED PLL Replacement Lamps directly replace compact fluorescent PLL lamps at a fraction of the energy cost.

Review all installation instructions and confirm use of a compatible ballast before installing EiKO Direct Fit Lamps.

FEATURES

- Directly replace 40W CFL PLL lamps
- Solid state replacement for 2' 40W PLL compact fluorescent lamps with 2G11 base
- Frosted lens for uniform diffuse appearance
- Up to 50% instant energy savings
- Instant-On with no warm up like fluorescents
- Suitable for use in totally enclosed fixtures
- No rewiring or modifications to fixture of any kind required
- Frosted glass lens reduces visual glare
- Not compatible with emergency ballasts
- Use of an incompatible ballast, poor socket connection or other improper installation can result in reduced lamp lifetime, arcing or localized overheating
- Note: check eiko.com for ballast compatibility

WARRANTY

- 5 year limited warranty; see eiko.com for warranty details

APPLICATIONS

- Retail
- Hospitality
- Office
- Ceiling Luminaires



RoHS
Compliant



cUL US LISTED

PERFORMANCE	Power Consumption	23W
	Lumens	2,600/2,800
	Efficacy (LPW)	113/122
	CRI	80+
	Beam	220°
	CCT	3000K, 3500K, 4000K, 5000K
	Life (L70)	50,000 hours
ELECTRICAL	Power Factor	≥0.9
	THD	<20%
	Input Voltage	120-277V
CONSTRUCTION	Operating Temperature	-4°F to 113°F (-20°C to 45°C)
	Base	2G11
LISTINGS	Certification(s)	cULus Listed; FCC
	Material Usage	RoHS Compliant; no mercury or lead
	Environment	UL Listed for damp locations

PERFORMANCE SUMMARY

Order Code	Item #	Lumens	Watts	CCT	CRI	MOL	Base	Life/Hours	Replaces Fluor
60461	LED23W/PLL/830-G7DR	2,600	23W	3000K	80+	22.2"	2G11	50K	40W CFL PLL
60462	LED23W/PLL/835-G7DR	2,600	23W	3500K	80+	22.2"	2G11	50K	40W CFL PLL
60463	LED23W/PLL/840-G7DR	2,800	23W	4000K	80+	22.2"	2G11	50K	40W CFL PLL
60464	LED23W/PLL/850-G7DR	2,800	23W	5000K	80+	22.2"	2G11	50K	40W CFL PLL

NOTE: Use order code when ordering.

DIMENSIONS

