



## TITLE 20/24 (JA8) LAMPS : MR16/DECORATIVE

### DESCRIPTION

These LED lamps are designed to meet or exceed the standards set out in the California Energy Commission's Title 20 and Title 24 (JA8) Appliance Efficiency Regulations.

### FEATURES

- MR16 GU5.3 and GU10 base
- 80% more efficient and 30x longer life than standard incandescent
- Shatter-resistant plastic housing for reduced risk of injury and breakage
- Compatible with a wide array of dimmers
- ANSI construction compliant

### WARRANTY

- 5 year limited warranty; see eiko.com for warranty details

### APPLICATIONS

- Recessed / Track Lighting
- Property Management
- Accent / Display Lighting
- Retail / Residential
- Healthcare
- Chandeliers
- Accent / display lighting
- Sconces
- Hospitality



MR16  
GU5.3 Base



MR16  
GU10 Base





<b>PERFORMANCE</b>	Bulb	MR16	
	Power Consumption	6.5W	
	Lumens	450	
	Efficacy (LPW)	69	
	CRI	90+	
	CCT	3000K	
	Life (L70)	25,000 hours	
<b>ELECTRICAL</b>	Power Factor	>0.9	
	Input Voltage	12V	120V
<b>CONSTRUCTION</b>	Operating Temperature	-4°F to 113°F (-20°C to 45°C)	
	Base	GU5.3	GU10
	Certification(s)	Title 20 and Title 24 (JA8) Compliant; ENERGY STAR® Rated; cULus Classified	
<b>LISTINGS</b>	Material Usage	RoHS Compliant; no mercury or lead	
	Environment	Suitable for damp locations; Enclosed fixture rated (select items); Not for use with electronic timers, photocells, or motion/occupancy sensors	

## PERFORMANCE SUMMARY

Order Code	Item #	Lumens	Watts	LPW	CCT	CRI	Beam	Base	Life/Hours	Replaces Incan.	ES
10677	LED6.5WMR16/FL/930-DIM-G8	450	6.5W	69	3000K	90+	40°	GU5.3	25,000	50W	★
10678	LED6.5WGU10/FL/930-DIM-G8	450	6.5W	69	3000K	90+	40°	GU10	25,000	50W	★

NOTE: Use order code when ordering. ★ENERGY STAR® Rated

## DIMENSIONS

<p>MR16 GU5.3</p> 	<table border="1"> <thead> <tr> <th>MOL</th> <th>MOD</th> </tr> </thead> <tbody> <tr> <td>1.77"/45mm</td> <td>1.97"/50mm</td> </tr> </tbody> </table>	MOL	MOD	1.77"/45mm	1.97"/50mm
MOL	MOD				
1.77"/45mm	1.97"/50mm				
<p>MR16 GU10</p> 	<table border="1"> <thead> <tr> <th>MOL</th> <th>MOD</th> </tr> </thead> <tbody> <tr> <td>2.17"/55mm</td> <td>1.97"/50mm</td> </tr> </tbody> </table>	MOL	MOD	2.17"/55mm	1.97"/50mm
MOL	MOD				
2.17"/55mm	1.97"/50mm				